



Valves | Single Check Valves | **Check Valves, Single**

H84X

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
H84X-200	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	200	(1375)	a
H84X-200	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	200	(1375)	a
H84X-250	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	250	(1720)	a
H84X-250	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	250	(1720)	a
H84X-300	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	a
H84X-300	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	300	(2065)	a
H84X-363	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	363	(2500)	a
H84X-363	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	363	(2500)	a
H84X-PN10	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	175	(1205)	a
H84X-PN10	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	175	(1205)	a



Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
H84X-PN16	Swing Check Valve Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	232	(1595)	a
H84X-PN16	Swing Check Valve Grooved Ends		76.1, 139.7, 165.1	232	(1595)	a

Remarks:

a. Resilient seat.

Details

Category	Check Valves, Single
Class of Work	1210 - Single Check Valves
Approval Standard	FM 1210 - Swing Check Valves
Certification Type	FM Approved
Listing Country	China

Company

Jinan Meide Casting Co Ltd

No.1 Meide Street, Meigui Town,
Pingyin County, Jinan City, China<http://meide-casting.com>