



Valves | Anti-Water Hammer Check Valves | **Check Valves, Anti-Water Hammer**

Model DH77XSR-300

Product Description

Resilient Seated Valves. The rated working pressure of the valves listed below is 300 psi (2065 kPa).

Product Specification

Model No	Valve Size		Flow Rate		Friction Loss	
	in	(mm)	gal/min	(dm³/min)	psi	(kPa)
DH77XSR-300	2	(50)	210	(795)	9.1	(63)
DH77XSR-300	2 1/2	(65)	300	(1135)	5.5	(38)
DH77XSR-300	3	(80)	460	(1740)	6.6	(45)
DH77XSR-300	4	(100)	795	(3010)	9.3	(64)
DH77XSR-300	5	(125)	1245	(4710)	7.7	(53)
DH77XSR-300	6	(150)	1800	(6815)	6.2	(43)
DH77XSR-300	8	(200)	3120	(11810)	3.0	(21)
DH77XSR-300	10	(250)	4915	(18605)	3.0	(21)
DH77XSR-300	12	(300)	7050	(26685)	3.8	(26)
DH77XSR-300	14	(350)	8450	(31985)	3.2	(22)
DH77XSR-300	16	(400)	11000	(41635)	4.1	(28)



Details

Category	Check Valves, Anti-Water Hammer
Class of Work	1230 - Anti-Wtr Hammer Ck Valves
Approval Standard	FM 1230 - Anti-Water Hammer Check Valves
Certification Type	FM Approved
Listing Country	China

Company

Jinan Meide Casting Co Ltd
No.1 Meide Street, Meigui Town,
Pingyin County, Jinan City, China
<http://meide-casting.com>