



1NS


Light-duty
Flexible Coupling



Nominal Size mm/in	Pipe O.D mm/in	Max Working Pressure PSI/MPa	Max. End Load kN/Lbs	Pipe End Separation mm/in	Dimensions			Bolt Size No.-Size mm/in	Certificate
					A mm/in	B mm/in	C mm/in		
50 2	60.3 2.37	300 2.07	5.9/1329	0-3.2 0-0.13	81.2 3.20	125 4.92	44.5 1.75	2-3/8X55 2-M10X57	UL
65 2 1/2	76.1 3.00	300 2.07	9.4/2117	0-3.2 0-0.13	96.5 3.79	138 5.43	44.5 1.75	2-3/8X55 2-M10X57	UL
80 3	88.9 3.500	300 2.07	12.8/2877	0-3.2 0-0.13	112.2 4.417	159 6.260	45.5 1.791	2-3/8X55 2-M10X57	UL
100 4	114.3 4.500	300 2.07	21.2/4770	0-3.2 0-0.13	139 5.47	182 7.16	50 1.97	2-3/8X55 2-M10X57	UL
125 5	139.7 5.500	450 3.10	47.5/10680	0-3.2 0-0.13	168 6.61	228 8.98	51 2.01	2-5/8X80 2-M16X85	UL
150 6	165.1 6.500	300 2.07	44.3/9960	0-3.2 0-0.13	192 7.56	244 9.61	51 2.01	2-1/2X75 2-M12X76	UL
150 6	168.3 6.625	300 2.07	46.0/10340	0-3.2 0-0.13	200 7.87	266 10.47	52 2.05	2-5/8X85 2-M16X85	UL
250 10	273.0 10.750	300 2.07	121.0/27210	0-3.2 0-0.13	320 12.60	398.0 15.67	64 2.52	2-3/4X120 2-M20X115	UL

1NX

Slim Type Flexible
Coupling



Nominal Size mm/in	Pipe O.D mm/in	Max Working Pressure PSI/MPa	Dimensions			Bolt Size No.-Size mm/in	Certificate
			A mm/in	B mm/in	C mm/in		
50 2	60.3 2.37	300 2.07	82.2 3.24	125 4.92	44.5 1.75	2-3/8X55 2-M10X57	UL
65 2 1/2	73.0 2 1/2	363 2.5	94.5 3.720	136 5.354	44.5 1.752	2-3/8X55 2-M10X57	UL
65 2 1/2	76.1 3.000	363 2.5	97.5 3.839	138 5.433	44.5 1.752	2-3/8X55 2-M10X57	—
80 3	88.9 3.500	363 2.5	110.4 4.346	152 5.984	45.5 1.791	2-3/8X55 2-M10X57	—
100 4	114.3 4.500	363 2.5	139 5.472	183 7.205	48 1.890	2-3/8X55 2-M10X57	—
125 5	139.7 5.5	363 2.5	165.4 6.50	220 8.86	49.5 1.95	2-1/2X70 2-M12X70	UL
150 6	165.1 6.500	363 2.5	194.1 7.642	249 9.803	50 1.969	2-1/2X70 2-M12X70	—
150 6	168.3 6.625	300 2.07	197 7.76	255 10.04	49.5 1.95	2-1/2X70 2-M12X70	UL
200 8	219.1 8.625	300 2.07	250 9.84	323 12.72	58.5 2.30	2-5/8X85 2-M16X85	UL
250 10	273.0 10.750	300 2.07	310 12.20	390 15.35	60 2.36	2-3/4X115 2-M20X115	UL FM