



# 1GKX


Slim Type Angle  
Pad Coupling



| Nominal<br>Size<br>mm/in | Pipe<br>O.D<br>mm/in | Max<br>Working<br>Pressure<br>PSI/MPa | Dimensions    |               |              | Bolt Size            | Certificate |
|--------------------------|----------------------|---------------------------------------|---------------|---------------|--------------|----------------------|-------------|
|                          |                      |                                       | A<br>mm/in    | B<br>mm/in    | C<br>mm/in   | No.-Size<br>mm/in    |             |
| 100<br>4                 | 114.3<br>4.500       | 300<br>2.07                           | 140.5<br>5.53 | 177.5<br>6.99 | 46.5<br>1.83 | 2-3/8X60<br>2-M10X63 | UL          |
| 150<br>6                 | 165.1<br>6.500       | 300<br>2.07                           | 195<br>7.68   | 240<br>9.45   | 49.5<br>1.95 | 2-1/2X70<br>2-M12X70 | UL          |
| 200<br>8                 | 219.1<br>8.625       | 300<br>2.07                           | 252<br>9.92   | 319<br>12.56  | 58<br>2.28   | 2-5/8X85<br>2-M16X85 | UL FM       |

# 3H

Standard  
Wrench Coupling



| Nominal<br>Size<br>mm/in | Pipe<br>O.D<br>mm/in | Max<br>Working<br>Pressure<br>PSI/MPa | Max. End<br>Load<br>kN/Lbs | Pipe End<br>Separation<br>mm/in | Dimensions  |              |             |
|--------------------------|----------------------|---------------------------------------|----------------------------|---------------------------------|-------------|--------------|-------------|
|                          |                      |                                       |                            |                                 | A<br>mm/in  | B<br>mm/in   | C<br>mm/in  |
| 80<br>3                  | 88.9<br>3.500        | 365<br>2.5                            | 15.5/3490                  | 0-3.2<br>0-0.13                 | 143<br>5.63 | 45.5<br>1.79 | 180<br>7.09 |