


130S


Light-duty Tee



Nominal Size mm/in	Pipe O.D mm/in	Max Working Pressure PSI/MPa	Dimensions L mm/in	Certificate
50 2	57.0 2.244	300 2.07	70 2.75	—
50 2	60.3 2.375	300 2.07	70 2.75	UL FM VdS LPCB
65 2½	73.0 2.875	300 2.07	76 3.00	UL FM
65 2½	76.1 3.000	300 2.07	76 3.00	UL FM VdS LPCB
80 3	88.9 3.500	300 2.07	85.5 3.37	UL FM VdS LPCB
100 4	108.0 4.500	500 3.45	101 3.98	UL FM
100 4	114.3 4.500	300 2.07	101 3.98	UL FM VdS LPCB
125 5	139.7 5.500	300 2.07	124 4.88	UL FM VdS LPCB
150 6	159.0 6.500	300 2.07	140 5.50	UL FM
150 6	165.1 6.500	300 2.07	140 5.50	UL FM LPCB
150 6	168.3 6.625	300 2.07	140 5.50	UL FM VdS LPCB
200 8	216.3 8.625	300 2.07	175 6.89	UL FM
200 8	219.1 8.625	300 2.07	175 6.89	UL FM VdS LPCB

130R

Reducing Tee



Nominal Size mm/in	Pipe O.D mm/in	Max Working Pressure PSI/MPa	Dimensions L mm/in	Dimensions L 1 mm/in	Certificate
65 × 65 × 80 2½ × 2½ × 3	76.1 × 76.1 × 88.9 3.000 × 3.000 × 3.500	500 3.45	108 4.25	95 3.74	—
65 × 65 × 100 2½ × 2½ × 4	76.1 × 76.1 × 114.3 3.000 × 3.000 × 4.500	500 3.45	127 5.00	102 4.02	—
80 × 80 × 100 3 × 3 × 4	88.9 × 88.9 × 114 3.500 × 3.500 × 4.500	500 3.45	127 5.00	102 4.02	—