


180R



Reducing Cross



Nominal Size mm/in	Pipe O.D mm/in	Max Working Pressure PSI/MPa	Dimensions L 1 mm/in	Dimensions L 2 mm/in	Certificate
65×50 2½×2	76.1×60.3 3.000×2.375	500 3.45	76 3.00	76 3.00	UL FM
80×50 3×2	88.9×60.3 3.500×2.375	500 3.45	85.5 3.37	85.5 3.37	UL FM
100×50 4×2	114.3×60.3 4.500×2.375	500 3.45	101 3.98	101 3.98	UL FM
100×80 4×3	114.3×88.9 4.500×3.500	500 3.45	101 3.98	101 3.98	UL FM
125×100 5×4	139.7×114.3 5.500×4.500	500 3.45	124 4.88	124 4.88	UL FM
159×108	159.0×108.0 6.250×4.250	500 3.45	124 4.88	124 5.50	UL FM
150×50 6×2	165.1×60.3 6.500×2.375	500 3.45	140 5.50	140 5.50	UL FM
150×65 6×2½	165.1×76.1 6.500×3.000	500 3.45	140 5.50	140 5.50	UL FM
150×80 6×3	165.1×88.9 6.500×3.500	500 3.45	140 5.50	140 5.50	UL FM
150×100 6×4	165.1×114.3 6.500×4.500	500 3.45	140 5.50	140 5.50	UL FM
150×50 6×2	168×60.3 6.625×2.375	500 3.45	140 5.50	140 5.50	UL FM
200×50 8×2	219.1×60.3 8.625×2.375	500 3.45	197 7.75	197 7.75	UL FM
200×100 8×4	219.1×108.0 8.625×4.250	500 3.45	175 6.89	175 6.89	—
200×100 8×4	219.1×114.3 8.625×4.500	500 3.45	175 6.89	175 6.89	UL FM
200×125 8×5	219.1×139.7 8.625×5.500	300 2.07	175 6.89	175 6.89	UL FM
200×150 8×6	219.1×159.0 8.625×6.250	300 2.07	175 6.89	175 6.89	UL FM
200×150 8×6	219.1×165.1 8.625×6.500	300 2.07	175 6.89	175 6.89	UL FM

180RX

Slim Type Reducing Cross



Nominal Size mm/in	Pipe O.D mm/in	Max Working Pressure PSI/MPa	Dimensions L1 mm/in	Dimensions L2 mm/in	Certificate
150×100 6×4	165.1×114.3 6.500×4.500	300 2.07	100 3.94	130 5.12	UL FM
150×100 6×4	168.3×114.3 6.625×4.500	300 2.07	100 3.94	130 5.12	UL FM
200×150 8×6	219.1×159.0 8.625×6.250	300 2.07	125.5 4.94	160 6.30	—
200×150 8×6	219.1×165.1 8.625×6.500	300 2.07	134 5.27	160 6.30	UL FM
200×150 8×6	219.1×168.3 8.625×6.625	300 2.07	134 5.27	160 6.30	UL FM