



181


Reducing Cross with Female Thread



Nominal Size mm/in	Pipe O.D mm/in	Max Working Pressure PSI/MPa	Dimensions L 1 mm/in	Dimensions L 2 mm/in	Certificate
65 × 50 2½ × 2	76.1 × 60.3 3.000 × 2.375	300 2.07	76 3.00	76 3.00	UL FM
80 × 32 3 × 1¼	88.9 × 42.4 3.500 × 1.660	300 2.07	108 4.25	108 4.25	—
80 × 40 3 × 1½	88.9 × 48.3 3.500 × 1.900	300 2.07	85.5 3.37	85.5 3.37	UL FM
80 × 50 3 × 2	88.9 × 60.3 3.500 × 2.375	300 2.07	85.5 3.37	85.5 3.37	UL FM
100 × 25 4 × 1	114.3 × 33.7 4.500 × 1.315	300 2.07	76 2.99	88 3.47	UL FM
100 × 32 4 × 1¼	114.3 × 42.4 4.500 × 1.660	300 2.07	76 2.99	88 3.47	UL FM
100 × 40 4 × 1½	114.3 × 48.3 4.500 × 1.900	300 2.07	85 3.35	91 3.58	UL FM
100 × 50 4 × 2	114.3 × 60.3 4.500 × 2.375	300 2.07	85 3.35	91 3.58	UL FM
100 × 65 4 × 2½	114.3 × 76.1 4.500 × 3.000	300 2.07	101 3.98	96 3.78	UL FM
100 × 80 4 × 3	114.3 × 88.9 4.500 × 3.500	300 2.07	101 3.98	96 3.78	UL FM
150 × 32 6 × 1¼	165.1 × 42.4 6.500 × 1.660	300 2.07	92 3.62	124 4.88	—
150 × 40 6 × 1½	165.1 × 48.3 6.500 × 1.900	300 2.07	92 3.62	124 4.88	UL FM
150 × 50 6 × 2	165.1 × 60.3 6.500 × 2.375	300 2.07	92 3.62	124 4.88	UL FM
150 × 65 6 × 2½	165.1 × 76.1 6.500 × 3.000	300 2.07	140 5.50	140 5.50	—
150 × 80 6 × 3	165.1 × 88.9 6.500 × 3.500	300 2.07	140 5.50	140 5.50	—
200 × 80 8 × 3	219.1 × 88.9 8.625 × 3.500	300 2.07	175 6.89	175 6.89	—

181RX

Slim Type Reducing Cross with Female Thread



Nominal Size mm/in	Pipe O.D mm/in	Max Working Pressure PSI/MPa	Dimensions L1 mm/in	Dimensions L2 mm/in	Certificate
150 × 80 6 × 3	165.1 × 88.9 6.500 × 3.500	300 2.07	93 3.66	123 4.84	UL FM
150 × 80 6 × 3	168.3 × 88.9 6.625 × 3.500	300 2.07	93 3.66	123 4.84	—