UL Product iQ®

Model/Configuration RC6

File Number: EX6624

COMPANY

JINAN MEIDE CASTING CO LTD
Meide Science and Technology Park
Pingyin Industrial Park
JINAN, Shandong Sheng 250400 China

MODEL/CONFIGURATION INFO

RC6
Malleable Iron Fittings

GENERAL

Dimensional Specification	Configuration	Size, in.	Pressure Class	Rated Pressure, psig (kPa)
EN 10242, "Threaded Pipe Fittings in Malleable Cast Iron" with ISO 7-1 threads	Extension piece, sockets M&F, reducing	3/8"X1/4",1/2x1/4,1/2x3/8,3/4x3/8, 3/4x1/2,1x1/2,1x3/4,1-1/4x1/2, 1-1/4x3/4,1-1/4x1,1-1/2x3/4,1-1/2x1, 1-1/2x1-1/4,2x1,2x1-1/4,2"X11/2"	--	500 (3447)
ISO 49, "Malleable Cast Iron Fittings Threaded to ISO 7-1"	Extension piece, sockets M&F, reducing	3/8"X1/4",1/2x1/4,1/2x3/8,3/4x3/8, 3/4x1/2,1x1/2,1x3/4,1-1/4x1/2, 1-1/4x3/4,1-1/4x1,1-1/2x3/4,1-1/2x1, 1-1/2x1-1/4,2x1,2x1-1/4,2"X11/2"	--	500 (3447)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."