



Model 321A  
File Number: EX6464

COMPANY

JINAN MEIDE CASTING CO LTD  
Meide Science and Technology Park  
Pingyin Industrial Park  
JINAN, Shandong Sheng 250400 China

MODEL INFO

321A  
Flange adapter

| COUPLINGS, FLANGE ADAPTERS |                                  |                                        |                            |
|----------------------------|----------------------------------|----------------------------------------|----------------------------|
| Outlet Type                | Pipe Type                        | Size, NPS (unless otherwise indicated) | Rated Pressure, psig (kPa) |
| Grooved, Rolled            | Sch. 10                          | 2, 2-1/2, 3, 4                         | 300 (2068)                 |
| Grooved, Rolled            | Sch. 10                          | 5                                      | 250 (1723)                 |
| Grooved, Cut               | 5.0 mm wall thickness            | 5                                      | 250 (1723)                 |
| Grooved, Rolled            | Sch. 10                          | 14                                     | 300 (2068)                 |
| Grooved, Cut               | Sch. 40                          | 14                                     | 300 (2068)                 |
| Grooved, Cut               | ISO 4200 (5.0 mm wall thickness) | 219.1 mm                               | 250 (1723)                 |
| Grooved, Cut               | ISO 4200 (6.3 mm wall thickness) | 273.0 mm, 323.9 mm                     | 250 (1723)                 |

NOTES

Notes

Suitable for use in dry pipe systems for temperatures to -40 F



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."