

Model 3GS

File Number: EX6464

COMPANY

JINAN MEIDE CASTING CO LTD

Meide Science and Technology Park

Pingyin Industrial Park

JINAN, Shandong Sheng 250400 China

MODEL INFO

3GS

Side outlet

SIDE OUTLETS				
Outlet Type	Outlet Pipe Type	Run Pipe Size, NPS (unless otherwise indicated)	Outlet Pipe Size, NPS (unless otherwise indicated)	Rated Pressure, psig (kPa)
--	--	8	2, 2-1/2, 76.1 mm, 3, 108.0 mm, 4	--
--	--	6	1-1/4, 1-1/2, 2, 2-1/2, 76.1 mm, 3	--
--	--	5	2	--
Grooved	Sch. 10, Sch. 40	3	1, 1-1/4, 1-1/2, 2	300 (2068)
--	--	4	1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1 mm, 3	--
Grooved	Sch. 10, Sch. 40	6	4	225 (1551)
Grooved	Sch. 10, Sch. 40	5	2-1/2, 3	400 (2757)
--	ISO 4200 (3.6 mm wall thickness)	139.7 mm	42.4 mm, 48.3 mm, 60.3 mm, 76.1 mm, 88.9 mm	--
Grooved	ISO 4200 (3.2 mm wall thickness)	133 mm	88.9 mm	300 (2068)
--	ISO 4200 (4.5 mm wall thickness)	159 mm	108.0 mm, 114.3 mm	--
Grooved	ISO 4200 (3.6 mm wall thickness)	139.7 mm	114.3 mm	175 (1206)

SIDE OUTLETS

Outlet Type	Outlet Pipe Type	Run Pipe Size, NPS (unless otherwise indicated)	Outlet Pipe Size, NPS (unless otherwise indicated)	Rated Pressure, psig (kPa)
Grooved	BS 1387 (M)	165 mm	42.4 mm, 48.3 mm, 60.3 mm, 76.1 mm, 88.9 mm	300 (2068)
Grooved	BS 1387 (M)	165 mm	108.0 mm, 114.3 mm	225 (1551)
Grooved	GB/T 21835	6-1/4 OD	3	300 (2068)

NOTES

Notes

Suitable for use in dry pipe systems for temperatures to -40 F

1 in. and larger nominal outlet sizes are intended for connection to custom piping

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."