



Model 3JS

File Number: EX6464

COMPANY

JINAN MEIDE CASTING CO LTD

Meide Science and Technology Park
Pingyin Industrial Park
JINAN, Shandong Sheng 250400 China

MODEL INFO

3JS
Side outlet

SIDE OUTLETS				
Outlet Type	Outlet Pipe Type	Run Pipe Size, NPS (unless otherwise indicated)	Outlet Pipe Size, NPS (unless otherwise indicated)	Rated Pressure, psig (kPa)
Threaded	Sch. 10, Sch. 40	3	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	300 (2068)
--	--	8	1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1 mm, 3, 4	--
--	--	6	1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1 mm, 3	--
--	--	4	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1 mm, 3	--
--	--	5	2	--
Threaded	Sch. 10, Sch. 40	6	4	225 (1551)
--	ISO 4200 (4.5 mm wall thickness)	159 mm	21.3 mm, 26.9 mm, 33.7 mm, 42.4 mm, 48.3 mm, 60.3 mm, 76.1 mm, 88.9 mm	--
--	ISO 4200 (3.6 mm wall thickness)	139.7 mm	21.3 mm, 26.9 mm, 33.7 mm, 42.4 mm, 48.3 mm, 60.3 mm, 76.1 mm, 88.9 mm	--
Threaded	ISO 4200 (3.6 mm wall thickness)	108 mm	21.3 mm, 26.9 mm, 33.7 mm, 42.4 mm, 48.3 mm, 60.3 mm, 76.1 mm	300 (2068)
--	ISO 4200 (3.2 mm wall thickness)	133 mm	21.3 mm, 26.9 mm, 33.7 mm, 42.4 mm, 48.3 mm, 60.3 mm, 76.1 mm, 88.9 mm	--

SIDE OUTLETS

Outlet Type	Outlet Pipe Type	Run Pipe Size, NPS (unless otherwise indicated)	Outlet Pipe Size, NPS (unless otherwise indicated)	Rated Pressure, psig (kPa)
--	ISO 4200 (4.5 mm wall thickness)	159 mm	114.3 mm	--
Threaded	ISO 4200 (3.6 mm wall thickness)	139.7 mm	114.3 mm	175 (1206)
Threaded	BS 1387 (M)	165 mm	21.3 mm, 26.9 mm, 33.7 mm, 42.4 mm, 48.3 mm, 60.3 mm, 76.1 mm, 88.9 mm	300 (2068)
Threaded	BS 1387 (M)	165 mm	114.3 mm	225 (1551)
Threaded	Sch. 10, Sch. 40	5	1-1/2	400 (2757)

NOTES

Notes

- Suitable for use in dry pipe systems for temperatures to -40 F
- 1/2 and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.
- 1 in. nominal outlet size is intended for direct connection to sprinklers.
- 1 in. and larger nominal outlet sizes are intended for connection to custom piping.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."