



Model 3L
File Number: EX6464

COMPANY

JINAN MEIDE CASTING CO LTD
Meide Science and Technology Park
Pingyin Industrial Park
JINAN, Shandong Sheng 250400 China

MODEL INFO

3L
Side outlet

SIDE OUTLETS				
Outlet Type	Outlet Pipe Type	Run Pipe Size, NPS (unless otherwise indicated)	Outlet Pipe Size, NPS (unless otherwise indicated)	Rated Pressure, psig (kPa)
Threaded	ISO 4200 (3.6 mm wall thickness)	42.4 mm	21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm	300 (2068)
--	ISO 4200 (3.2 mm wall thickness)	60.3 mm	21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm	--
--	ISO 4200 (3.6 mm wall thickness)	76.1 mm	21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm	--
--	ISO 4200 (3.2 mm wall thickness)	88.9 mm	33.7 / 3.2 mm	--
--	ISO 4200 (3.2 mm wall thickness)	73 mm	21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm	--
--	ISO 4200 (4.0 mm wall thickness)	48.3 mm	21.3 / 2.8 mm, 26.9 / 2.9 mm, 33.7 / 3.2 mm	--

NOTES

Notes

Suitable for use in dry pipe systems for temperatures to -40 F

NOTES

Notes

1/2 and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.

1 in. and larger nominal outlet sizes are intended for connection to custom piping.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."