Heat-automatic Fire Detectors

COMPANY
Eaton Electrical Products Ltd
Llantarnam Park
Cwmbran, NP44 3AW United Kingdom

S35887

Model No.	Type	Compatibility Restrictions	Contact Arrangement	Temp Range (°F)	Spacing (Ft) Smooth Ceiling	Spacing (Ft) to Wall or Partition
UCHR-2W	FT/ROR	D2	-	135	50	25
UCHRI-2W	FT/ROR	D2	-	194	50	25
UCHT-2W	FT	D2	-	135	50	25
UCHTI-2W	FT	D2	-	194	50	24
ULCAH330(**)(c), ULMAH330(**)(a)(c), ULFX330(**)(b)(c)	FT/ROR	D2	-	135, 194	50	25

Base Model	Related Detector	Control Unit Compatibility Restrictions
CB, CB2E	UCPD-2W, UCPT-2W, UCPTR-4W	B2
WBA, UCAB300	ULCAP320, ULMAP320, ULFX320, ULCAPT340, ULMAPT340, ULFX340	B2

B2 - For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.

D2 - For connection to Listed control units with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for detector (base) and/or control unit.

FT/ROR - Fixed temperature/rate of rise combination

FT - Fixed temperature

Cookies on UL Solutions
We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. Learn more
Cookies Settings | Reject All | Accept All Cookies

Note - Detector model UCHR-2W, UCHRI-2W, UCHT-2W, UCHTI-2W are Compatible with Detector Bases CB and CB2E and Detector Model s UCAH330, ULCAH330, ULMAH330 and ULFX330 are Compatible with Bases WBA and UCAB300

Trademark and/or Tradename: "Cooper", "JSB", "Menvier", 

Last Updated on 2024-08-28

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. Learn more