FM Approvals

Valves | Angle Hose Valves | Hose Valves, Angle

Models A55H, A56H, A155, A156, A156G, A55E, A55EG, A56E, A56EG

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
A55H	Standard Hose Valves Grooved x Female Connection Female Connection x Female Connection	2 1/2	(64)	500	(3445)	
A56H	Grooved x Male Connection Female Connection x Male Connection	2 1/2	(64)	500	(3445)	
A155	Pressure Restricting Hose Valve Standard Hose Valves Female Connection x Female Connection	1 1/2, 2 1/2	(38, 64)	300	(2070)	a
A156	Pressure Restricting Hose Valve Female Connection x Male Connection	1 1/2, 2 1/2	(38, 64)	300	(2070)	a
A156G	Standard Hose Valves Grooved x NYCT	2 1/2	(64)	300	(2070)	a
A55E	Standard Hose Valve Female x Female NPT	1 1/2, 2 1/2	(38, 64)	300	(2070)	
A55EG	Standard Hose Valve Groove x Female NPT	2 1/2	(64)	300	(2070)	
A56E	Standard Hose Valve Male NHT x Female NPT	1 1/2, 2 1/2	(38, 64)	300	(2070)	
A56EG	Standard Hose Valve Groove x Male NHT	2 1/2	(64)	300	(2070)	

Remarks:

a. For pressure restricting hose valve settings review operation manual.

Details

Category	Hose Valves, Angle
Class of Work	1521 - Angle Hose Valves

Company

Giacomini SpA
Via per Alzo 39, 28017 San Maurizio d'Opaglio (NO) Italy
http://giacomini.com

Approvals

Approval Standard	FM 1521, 1522 - Angle and Straightaway Hose Valves
Certification Type	FM Approved
Listing Country	Italy

FM Approvals

Additional Info

Hydrants & Hoses

Hose Valves

Hose valves of 1 ½ in. (38 mm) may be used on connections from sprinkler systems; 2 ½ in. (64 mm) valves are used on hose standpipes and fire pump headers. For pressures above 175 psi (1205 kPa), an appropriate pressure reducing device shall be used.

Hose Valves, Angle