Model PRV-1A

File Number: EX6886

COMPANY

TYCO FIRE & BUILDING PRODUCTS
1467 ELMWOOD AVE
CRANSTON, RI 02910-3849 United States

MODEL INFO

PRV-1A
Pilot-operated pressure control valve

VALVE INFORMATION

Body Type	Nominal Pipe Size (NPS)	End Configuration, Inlet by Outlet	Max Rated Pressure, psig (kPa)	Outlet Pressure-setting Range, psig (kPa)
Globe	2	Flanged, Grooved	300 (2068)	80 - 175
Globe	3	Flanged, Grooved	300 (2068)	80 - 175
Globe	4	Flanged, Grooved	300 (2068)	90 - 175
Globe	6	Flanged, Grooved	300 (2068)	80 - 175

GENERAL

Installation Limitations

End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

The manufacturer's design and installation instructions include a description of performance characteristics for both flowing and static conditions.

Pressure ratings of components installed downstream shall not be exceeded.

Report Date: 2020-02-25
Revision Date: 2026-03-26

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."