UL Solutions | Product iQ®

SIN TY5137

File Number: EX5985

COMPANY

TYCO FIRE & BUILDING PRODUCTS
1467 ELMWOOD AVE
CRANSTON, RI 02910-3849 United States

SIN INFO

TY5137
Glass Bulb Type

ATTRIBUTES

Response Type	Sprinkler Type	Nom K-Factor, gpm/vpsi (L/min/vbar)	System Working Pressure	Corrosion Resistant
QR	Extended Coverage Sprinklers - Ordinary Hazard (ECOH)	11.2 (160)	175 psig (1.2 Mpa)	Non-Wax Coatings - See installation instructions

GENERAL

Inlet Connection

3/4 in. NPT

EXTENDED COVERAGE SPRINKLERS - ORDINARY HAZARD (ECOH)

Type	Max Width x Length, ft x ft (m x m)	Ordinary Hazard Group	Obstructed Construction?	Min Flow, GPM (LPM)	Sprinkler Temp Rating, °F (°C)	Cover Temp Rating, °F (°C)
Upright	14 x 14 (4.3 x 4.3)	1	No	30 (114)	135 (57), 155 (68), 175 (79), 200 (93), 286 (141)	Not Applicable
Upright	14 x 14 (4.3 x 4.3)	2	No	39 (148)	135 (57), 155 (68), 175 (79), 200 (93), 286 (141)	Not Applicable

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on

the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."