SIN TY3532

File Number: EX5985

COMPANY

TYCO FIRE & BUILDING PRODUCTS
1467 ELMWOOD AVE
CRANSTON, RI 02910-3849 United States

SIN INFO

TY3532
Glass Bulb Type

ATTRIBUTES

Response Type	Sprinkler Type	Nom K-Factor, gpm/vpsi (L/min/vbar)	System Working Pressure	Corrosion Resistant
QR	Extended Coverage Sprinklers - Light Hazard (ECLH)	5.6 (80)	175 psig (1.2 Mpa)	Not Available

GENERAL

Inlet Connection

1/2 in. NPT

EXTENDED COVERAGE SPRINKLERS - LIGHT HAZARD (ECLH)

Type	Distance Below Ceiling, in. (cm)	Max Width x Length, ft x ft (m x m)	Min Flow, GPM (LPM)	Sprinkler Temp Rating, °F (°C)	Cover Temp Rating, °F (°C)
Conc. Pendent	--	16 x 16 (4.9 x 4.9)	26 (98)	155 (68)	139 (59)
Conc. Pendent	--	16 x 16 (4.9 x 4.9)	26 (98)	200 (93)	165 (73)
Conc. Pendent	--	20 x 20 (6.1 x 6.1)	40 (151)	155 (68)	139 (59)
Conc. Pendent	--	20 x 20 (6.1 x 6.1)	40 (151)	200 (93)	165 (73)
Conc. Pendent	--	18 x 18 (5.5 x 5.5)	33 (125)	155 (68)	139 (59)

EXTENDED COVERAGE SPRINKLERS - LIGHT HAZARD (ECLH)

Type	Distance Below Ceiling, in. (cm)	Max Width x Length, ft x ft (m x m)	Min Flow, GPM (LPM)	Sprinkler Temp Rating, °F (°C)	Cover Temp Rating, °F (°C)
Conc. Pendent	--	18 x 18 (5.5 x 5.5)	33 (125)	200 (93)	165 (73)

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."