UL Product iQ®

Model AV-1-300

File Number: EX6872

COMPANY

TYCO FIRE & BUILDING PRODUCTS

1467 ELMWOOD AVE
CRANSTON, RI 02910-3849 United States

MODEL INFO

AV-1-300
Alarm Valve

PRODUCT INFORMATION

Body Type	Nom Pipe Size, NPS	End Configuration	Max Rated Pressure, psig (kPa)	Supply Pressure Type	Alarm Device Type	Alarm Device Model	Retard Chamber Model	Installed Position
Globe	2-1/2, 4, 6, 8	Flange, Flange by Groove, Groove	300 (2068)	Variable	Water motor gong	WMA-1	RC-1	Horizontal, Vertical
Globe	2-1/2, 4, 6, 8	Flange, Flange by Groove, Groove	300 (2068)	Variable	Electric pressure switch	UL Listed (VOXZ)	RC-1	Horizontal, Vertical
Globe	2-1/2, 4, 6, 8	Flange, Flange by Groove, Groove	300 (2068)	Constant	Water motor gong	WMA-1	Not Applicable	Horizontal, Vertical
Globe	2-1/2, 4, 6, 8	Flange, Flange by Groove, Groove	300 (2068)	Constant	Electric pressure switch	UL Listed (VOXZ)	Not Applicable	Horizontal, Vertical

NOTES

Additional Model Notes

May be provided with flanged connections drilled per ANSI, AS, ISO, and JIS specifications.

Model WMA-1 "Y" strainer for rated pressures not exceeding 300 psig.

Cookies on UL Solutions
We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. Learn more
Cookies Settings Reject All Accept All Cookies

GENERAL

Installation Limitations

End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. Learn more